




CUSTOM RECTANGLE DAMPERS




- Available in Millivolt (FSM) and 24v(FSE) models
- Custom sizing from 4" to 16"
- Call for help with sizing, have "X" shape inner corner to corner measurements
- In general, the size requested should be 1/4" less on both the length and width
- Prices based on standard units, using longest side as unit price.
- A Flue Sentinel Custom Ordering Form must be used when ordering.

Be AWARE: there must be a clearance of at least 4" below the damper blade to allow for rotation without interference.







Estimated Measurements Only

ALL DIMENSIONS ARE IN INCHES

	"A"	"B"	"C"	"D"	"E"	"F"
MODEL	Pipe	Pipe	Height	Overall	Overall	Overall
	Width	Length	Above	Height	Width	Length
FS(E,M) 4 x	4.0	4 to 16	7.8	9.0	10.0	10 to 22
FS(E,M) 5 x	5.0	5 to 16	7.8	9.0	11.0	11 to 22
FS(E,M) 6 x	6.0	6 to 16	7.8	9.0	12.0	12 to 22
FS(E,M) 7 x	7.0	7 to 16	7.8	9.0	13.0	13 to 22
FS(E,M) 8 x	8.0	8 to 16	7.8	9.0	14.0	14 to 22
FS(E,M) 9 x	9.0	9 to 16	7.8	9.0	15.0	15 to 22
FS(E,M) 10 x	10.0	10 to 16	8.3	10.0	16.0	16 to 22
FS(E,M) 11 x	11.0	11 to 16	8.8	10.0	17.0	17 to 22
FS(E,M) 12 x	12.0	12 to 16	9.3	10.0	18.0	18 to 22
FS(E,M) 13 x	13.0	13 to 16	9.8	10.0	19.0	19 to 22
FS(E,M) 14 x	14.0	14 to 16	10.3	11.5	20.0	20 to 22
FS(E,M) 15 x	15.0	15 to 16	10.8	12.0	21.0	21 to 22
FS(E,M) 16 x	16.0	16 to 16	11.3	12.5	22.0	22 to 22