

BENEFITS

Musty odors and "dirty sock syndrome" can be a problem in air handlers and rooftops. The air conditioning coil component of these systems can become a breeding ground for mold and fungi which will create a toxic biofilm reducing operational efficiency and cause poor indoor air. Field Controls CommercialUV CUV systems are designed to prevent toxic biofilm build up on AC-coils and significantly reduce airborne germs, viruses, and bacteria.

FEATURES

| \bigcirc | Eradicates cooling coil biofilms |
|-------------------|--|
| \Diamond | Reduces HVAC system operating costs and maintenance |
| \Diamond | Multiple lengths for your applications (18", 23", 28", 34", 38", 46", & 58" options) |
| \Diamond | Intensity ranges from 278 - 780 µW/cm ² @1m |
| \Diamond | Zero ozone means pure air delivery |
| \Diamond | 2-year/18,000 hr. lamp life for durability you can trust |
| \Diamond | UVC shut-off for service and maintenance |
| $\overline{\Box}$ | Liquid Crystal Displays provide lamp and ballast status |




HOW IT WORKS


The Field Controls CommercialUV CUV series radiates High Output UVC energy at the 253.7 nanometer wavelength. The CUV series compliments an HVAC filtration system and provides cost effective coil irradiation and air treatment disinfection free of hazardous ozone. Ultraviolet Germicidial Irradiation (UVGI) enery is the perfect solution for irradiating air conditionig coils and the air stream to inactivate microbial organisms such as fungi, mold, bacteria, and viruses. The result will yield mold-free coils, toxin-free indoor air, and efficient airflow maintainig peak HVAC equipment efficiency. Install a Field Controls CommercialUV system and start improving indoor air quality today.



| COMMERCIAL UV MODELS | | | |
|----------------------|------------|--|--|
| Part Number Model | | Description | |
| 602651702 | CUV-1118DN | 17.5" (2) Lamp Non-Coated Commercial UVC High Output 120-277 VAC | |
| 602652302 | CUV-1123DN | 23" (2) Lamp Non-Coated Commercial UVC High Output 120-277 VAC | |
| 602652312 | CUV-1123DC | 23" (2) Lamp Coated Commercial UVC High Output 120-277 VAC | |
| 602652801 | CUV-1128SN | 28" (1) Lamp Non-Coated Commercial UVC High Output 120-277 VAC | |
| 602652802 | CUV-1128DN | 28" (2) Lamp Non-Coated Commercial UVC High Output 120-277 VAC | |
| 602652811 | CUV-1128SC | 28" (1) Lamp Coated Commercial UVC High Output 120-277 VAC | |
| 602652812 | CUV-1128DC | 28" (2) Lamp Coated Commercial UVC High Output 120-277 VAC | |
| 602653401 | CUV-1134SN | 34" (1) Lamp Non-Coated Commercial UVC High Output 120-277 VAC | |
| 602653402 | CUV-1134DN | 34" (2) Lamp Non-Coated Commercial UVC High Output 120-277 VAC | |
| 602653411 | CUV-1134SC | 34" (1) Lamp Coated Commercial UVC High Output 120-277 VAC | |
| 602653412 | CUV-1134DC | 34" (2) Lamp Coated Commercial UVC High Output 120-277 VAC | |
| 602653802 | CUV-1538DN | 38" (2) Lamp Non-Coated Commercial UVC High Output 120-277 VAC | |
| 602653812 | CUV-1538DC | 38" (2) Lamp Coated Commercial UVC High Output 120-277 VAC | |
| 602654602 | CUV-1546DN | 46" (2) Lamp Non-Coated Commercial UVC High Output 120-277 VAC | |
| 602654612 | CUV-1546DC | 46" (2) Lamp Coated Commercial UVC High Output 120-277 VAC | |
| 602655802 | CUV-1558DN | 58" (2) Lamp Non-Coated Commercial UVC High Output 120-277 VAC | |
| 602655812 | CUV-1558DC | 58" (2) Lamp Coated Commercial UVC High Output 120-277 VAC | |







AC-coils without AC-coils with Germicidal Irradiation



CommercialUV installed

